

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/754,937	01/09/2004	Ryuichi Takechi	FUJY 20.856	7408
26304 KATTEN MU	7590 11/01/2007 CHIN ROSENMAN LLP	•	EXAMINER	
575 MADISON AVENUE		•	RIVAS, SALVADOR E	
NEW YORK,	NY 10022-2585		ART UNIT PAPER NUMBER	
			2619	
	,		MAIL DATE	DELIVERY MODE
		•	11/01/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)	<del></del>
	10/754,937	TAKECHI ET AL.	
Office Action Summary	Examiner	Art Unit	
	Salvador E. Rivas	2616	
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with th	ne correspondence addres	s
• •	V. 10. 057 70. 5V5155 - 110.V5		
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING Description of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication.  If NO period for reply is specified above, the maximum statutory period Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICAT 136(a). In no event, however, may a reply b will apply and will expire SIX (6) MONTHS te, cause the application to become ABAND	TON.  be timely filed  from the mailing date of this communioned (35 U.S.C. § 133).	·
Status	•		
1) Responsive to communication(s) filed on 30 J	luly 2007.		
2a) This action is <b>FINAL</b> . 2b) ⊠ This	s action is non-final.		
3) Since this application is in condition for allowa	ance except for formal matters,	prosecution as to the me	rits is
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D. 11	, 453 O.G. 213.	:
Disposition of Claims			
4) Claim(s) 1-9 is/are pending in the application.			
4a) Of the above claim(s) is/are withdra		<u>.</u>	
5) Claim(s) is/are allowed.	•		
6)⊠ Claim(s) <u>1-9</u> is/are rejected.		•	
7) Claim(s) is/are objected to.			
8) Claim(s) are subject to restriction and/o	or election requirement.		
Application Papers	•		
9) The specification is objected to by the Examine	er		
10)⊠ The drawing(s) filed on 30 July 2007 is/are: a)		to by the Examiner.	
Applicant may not request that any objection to the	• • • • • • • • • • • • • • • • • • • •		
Replacement drawing sheet(s) including the correct			121(d).
11)☐ The oath or declaration is objected to by the E	xaminer. Note the attached Off	fice Action or form PTO-1	52.
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign	n priority under 35 U.S.C. § 119	9(a)-(d) or (f).	
a) ☐ All b) ☐ Some * c) ☐ None of:	, promy ander de droid, gran		
1. Certified copies of the priority documen	ts have been received.		
2. Certified copies of the priority documen	ts have been received in Applic	cation No	
3. Copies of the certified copies of the price	ority documents have been rece	eived in this National Stag	je
application from the International Burea			
* See the attached detailed Office action for a list	t of the certified copies not rece	eived.	
••	,		-
Attachment(s)	٠		
1) Notice of References Cited (PTO-892)	4) Interview Summ		
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(s)/Ma 5) Notice of Inform		
Paper No(s)/Mail Date	6) Other:	••	

Art Unit: 2616

9. -- -- - 9

### **DETAILED ACTION**

Page 2

This Action is in response to Applicant's amendments filed on July 30, 2007.
 Claims 1-9 are now pending in the present application. This Action is made NON-FINAL.

## **Drawings**

2. The drawings are objected to as failing to comply with 37 CFR 1.84(p)(4) because reference characters "1" and "7a" have both been used to designate lpv4- lpv6 TRANSLATION DEVICE. Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

# Claim Rejections - 35 USC § 112

3. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Art Unit: 2616

**Claim 1** is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Regarding claim 1, page 2 lines 9-10 state the following limitation: "a replacing unit replacing the address in the second network read by the reading unit with the source address of the data" renders the claim indefinite because the addition of the phrase "the address in the second network" and the words "source address" to an otherwise definite expression extends the scope of the expression so as to render it indefinite (*Ex parte Copenhaver*, 109 USPQ 118 (Bd. App. 1955)). See MPEP § 2173.05 (b)

It is suggested that the applicant replace the limitation with: "a replacing unit replacing the ID in the first network read by the reading unit with the address in the second network of the data"

### Claim Rejections - 35 USC § 103

- 4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation

Art Unit: 2616

under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

The factual inquiries set forth in *Graham* v. *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- 1. Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent art.
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Claims 1-9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hamamoto et al. (U.S. Patent # 6,038,233) in view of Asano et al. (U.S. Patent Application Publication # 2003/0185236 A1).

Regarding claim 1, Hamamoto et al. teach an address translation device (read as Ipv6/Ipv4 translator (Fig.1 @ 55), Column 6 Line 5-6) comprising: an extraction unit (read as an header translation unit (Fig.2 @ 33)) extracting, from data received via a first network (read as IPv6 Network (Fig.1 @ 52)), a fixed identifier indicating a transmission source of the data ("The header translation unit 33, upon receiving the packet, extracts the IPv6 address, which is the source IP address, included in the packet, and searches for an IPv4 address which has previously corresponded to the extracted IPv6 address ...", Column 8 Lines 3-7); a storage unit (read as an address translation information table (Fig. 2 @ 35)) storing the fixed identifier and an address

(Fig. 2 @ 35 is used to store "... address translation information", Column 6, Line 25), in a second network (read as IPv4 Network (Fig.1 @ 54)), of the transmission source indicated by the fixed identifier by relating fixed identifier and the address each other ("the address translation processing unit 43 assigns a certain IPv4 address to the aforementioned IPv6 address.", Fig.8, Column 10 Lines 39-41); a reading unit (read as IPv4/v6 reception processing unit (Fig.2 @ 31)) reading the address, in the second network, stored on the storage unit and related to the fixed identifier extracted by the extraction unit ("a header translation unit 33 for translating the header of a packet fetched by the IPv4/v6 reception processing unit 31 based on address translation information stored in an address translation information table 35 and for updating the contents of the address translation information table 35 as required", Column 6 Lines 22-27); a replacing unit (read as an address translation information exchange unit (Fig.2 @ 34)) replacing the address in the second network read by the reading unit with the source address of the data (Fig.2 @ 34 "for exchanging the address translation information stored in the address translation information table 35 with address translation information stored in a particular node connected to the IPv4 network 54.", Column 6 Lines 30-34). However, Hamamoto et al. fails to teach an identifier extraction unit extracting a variable address of a terminal device connected to the first network and the fixed identifier, from the data received via the first network; an identifier storage unit storing the variable address and the fixed identifier extracted by the identifier extraction unit by relating the variable address and the fixed identifier; a variable address acquisition unit acquiring, from the storage unit and the identifier storage unit, the

Art Unit: 2616

variable address corresponding to a destination address of the data addressed to the terminal device, which contains, as a destination address, the address in the second network received via the second network and an adding unit adding the variable address acquired by the variable address acquisition unit, as the destination address of the received data, and adding the fixed identifier related with the variable address stored by the identifier storage unit, to the received data.

Asano et al. illustrates a case wherein the identifier receiving unit (read as home agent (Fig.2 @ 20)) receiving data containing a variable address (read as a care-of address) of an IPv6 terminal device and the fixed identifier (read as home address) indicating the IPv6 terminal device ("Mobile IPv6 ... has two IP addresses as shown in FIG. 2: home address and care-of address.", paragraph [0008], Lines 1-3 and [0015]); an identifier storage unit (read as a home agent) storing the care-of address and the fixed identifier (read as a home address) that have been received by the identifier receiving unit by relating to the care-of address and the fixed identifier (read as a home address) each other (the home agent incorporates a "storage section to memorize an address management table, which defines the relationship between the home address and care-of address.", [0008] Lines 6-8); a variable address acquisition unit (read as home agent (Fig.2 @ 20)) acquiring, from the storage unit and the identifier storage unit, the variable address(read as a care-of address) corresponding to a destination address of the data addressed to the terminal device, which contains, as a destination address, the address in the second network received via the second network ("If the Mobile IPv6 terminal 10 moves subsequently (S50), the home agent registers the

in the address 22 and a new care-of address 23, which results from a move, in the address management table, and sends an acknowledgment packet back to the Mobile IPv6 terminal 10(S70)", paragraph [0013] Lines 11-14) and an adding unit adding the variable address acquired by the variable address acquisition unit, as the destination address of the received data, and adding the fixed identifier related with the variable address stored by the identifier storage unit, to the received data. It would have been obvious to a person of ordinary skill in the art to combine the home agent of Asano et al. in with the translator of Hamamoto et al. for the purpose of coupling two distinct networks having different addressing architectures. The motivation being to efficiently exchange a data communication path and couple an IPv4 terminal to intercommunicate to a Mobile IPv6 terminal and vice versa.

However, Hamamoto et al. and Asano et al. does not explicitly teach an adding unit adding the variable address acquired by the variable address acquisition unit, as the destination address of the received data, and adding the fixed identifier related with the variable address stored by the identifier storage unit, to the received data. It would have been obvious to a person of ordinary skill in the art to incorporate the functionality of an adding unit (taught by Asano et al.'s home agent (Fig. 2@ 20) in with the translation device ((Fig.1 @ 55) as taught by Hamamoto et al.) for the purpose of coupling two distinct networks having different addressing architectures. Lacking any criticality, to make prior art parts integral does not make the claimed invention patentable over the prior art. MPEP § 2144(V)(B) (Citing to *In re Larson*, 340 F.2d 965, 968, 144 USPQ 347, 349 (CCPA 1965)).

Art Unit: 2616

Regarding claim 3, Hamamoto et al. clearly shows and discloses a packet translation device, interposed between an IPv6 (Internet Protocol version 6) network and an IPv4 (Internet Protocol version 4) network, for mutually translating an IPv4 packet and an IPv6 packet (inherently taught by Ipv6/Ipv4 translator (Fig.1 @ 55) and Column 6 Lines 5-6), comprising: an extraction unit extracting, from the IPv6 packet, a fixed identifier indicating a transmission source of the IPv6 packet ("The header translation unit 33, upon receiving the packet, extracts the IPv6 address, which is the source IP address, included in the packet, and searches for an IPv4 address which has previously corresponded to the extracted IPv6 address ...", Column 8 Lines 3-7); a storage unit (read as an address translation information table (Fig. 2 @ 35)) storing the fixed identifier and an IPv4 address assigned to the transmission source by relating the fixed identifier and an IPv4 address each other (Fig.2 @ 35 is used to store "... address translation information", Column 6, Line 25); a reading unit (read as IPv4/v6 reception processing unit (Fig.2 @ 31)) reading the IPv4 address stored on the storage unit (read as an address translation information table (Fig. 2 @ 35)) and related to the fixed identifier extracted by the extraction unit (Fig.2 @ 35 is used to store "... address translation information", Column 6, Line 25); and a packet translating unit translating the IPv6 packet into the IPv4 packet with the IPv4 address read by the reading unit being set as a source address ("a header translation unit 33 for translating the header of a packet fetched by the IPv4/v6 reception processing unit 31 based on address translation information stored in an address translation information table 35 and for updating the contents of the address translation information table 35 as required",

Art Unit: 2616

Column 6 Lines 22-27); wherein the packet translating unit (read as translator (Fig.1 @ 55)) translates the IPv4 packet into an IPv6 packet ("the header translation unit 33 sets an IPv4-mapped-IPv6 address "::ffff:133.144.95.22" of the IPv4 host 53 as the source IP address and the previously extracted IPv6 address "::1234:5678:9abc" as the destination IP address in the packet.", Column 11 Lines 31-35). However, Hamamoto et al. fails to teach an identifier receiving unit receiving data containing a care-of address of an IPv6 terminal device and the fixed identifier indicating the IPv6 terminal device; an identifier storage unit storing the care-of address and the fixed identifier that have been received by the identifier receiving unit by relating to the care-of address and the fixed identifier each other; a care-of address acquisition unit acquiring the care-of address corresponding to a destination address of the received IPv4 packet from the storage unit and from the identifier storage unit, with the care-of address acquired by the care-of address acquisition unit being set as a destination address, and with the fixed identifier related with the care-of address stored by the identifier storage unit.

Asano et al. illustrates a case wherein the identifier receiving unit (read as home agent (Fig.2 @ 20)) receiving data containing a care-of address of an IPv6 terminal device and the fixed identifier (read as home address) indicating the IPv6 terminal device ("Mobile IPv6 ... has two IP addresses as shown in FIG. 2: home address and care-of address.", paragraph [0008], Lines 1-3 and [0015]); an identifier storage unit (read as a home agent) storing the care-of address and the fixed identifier (read as a home address) that have been received by the identifier receiving unit by relating to the care-of address and the fixed identifier (read as a home address) each other (the home

agent incorporates a "storage section to memorize an address management table. which defines the relationship between the home address and care-of address.", [0008] Lines 6-8); a care-of address acquisition unit (read as home agent (Fig.2 @ 20)) acquiring the care-of address corresponding to a destination address of the received IPv4 packet from the storage unit and from the identifier storage unit, with the care-of address acquired by the care-of address acquisition unit being set as a destination address, and with the fixed identifier related with the care-of address stored by the identifier storage unit ("If the Mobile IPv6 terminal 10 moves subsequently (\$50), the home agent registers the invariable home address 22 and a new care-of address 23, which results from a move, in the address management table, and sends an acknowledgment packet back to the Mobile IPv6 terminal 10(S70)", paragraph [0013] Lines 11-14). It would have been obvious to a person of ordinary skill in the art to combine the home agent of Asano et al. in with the translator of Hamamoto et al. for the purpose of coupling two distinct networks having different addressing architectures. The motivation being to efficiently exchange a data communication path and couple an IPv4 terminal to intercommunicate to a Mobile IPv6 terminal and vice versa.

Regarding **claim 5**, and **as applied to claim 3 above**, Asano et al., as modified by Hamamoto et al., teach a packet translation device (Fig.1 @40) wherein the fixed identifier is a home address of the IPv6 terminal device ("Mobile IPv6 ... has two IP addresses as shown in FIG. 2: home address and care-of address.", paragraph [0008], Lines 1-3 and [0015]).

Art Unit: 2616

Regarding claim 6, and as applied to claim 3 above, Hamamoto et al., as modified by Asano et al., further discloses a packet translation device (inherently taught by Ipv6/Ipv4 translator (Fig. 1 @ 55) and Column 6 Line 5-6), wherein the storage unit further stores a port number by relating the port number, the address and the fixed identifier each other (Column 13 Lines 48-63), and wherein the reading unit reads the IPv4 address and the source port number stored on the storage unit and related to the fixed identifier extracted by the extraction unit (Column 6 Lines 22-27)

Regarding claim 7, and as applied to claim 6 above, Hamamoto et al. clearly shows and discloses a packet translation device (read as Ipv6/Ipv4 translator (Fig.1 @ 55) and Column 6 Line 5-6). However, Hamamoto et al. fails to teach wherein the care-of address acquisition unit acquires, from the storage unit and the identifier storage unit, a care-of address corresponding to the destination address and the destination port number of the IPv4 packet received.

Asano et al. teach a case where the care-of address acquisition unit (taught by home agent 20 (Fig.2)) acquires, from the storage unit and the identifier storage unit (read as address management table [0016]), a care-of address corresponding to the destination address and the destination port number of the IPv4 packet received ([0015]-[0016]). It would have been obvious to a person of ordinary skill in the art at the time of the invention was made to have a Mobile Ipv6 terminal to send notice of a care of address via a home agent as shown by Asano et al. in the translator of Hamamoto et al. for the purpose of coupling two distinct networks having different addressing architectures. The motivation being to

Art Unit: 2616

Regarding claims 8 and 9, Hamamoto et al. clearly shows and discloses a packet translation device, interposed between an IPv6 (Internet Protocol version 6) network and an IPv4 (Internet Protocol version 4) network, for mutually translating an IPv4 packet and an IPv6 packet (inherently taught by Ipv6/Ipv4 translator (Fig.1 @ 55) and Column 6 Lines 5-6), comprising: an extraction unit extracting, from the IPv6 packet, a fixed identifier indicating a transmission source of the IPv6 packet ("The header translation unit 33, upon receiving the packet, extracts the IPv6 address, which is the source IP address, included in the packet, and searches for an IPv4 address which has previously corresponded to the extracted IPv6 address ...", Column 8 Lines 3-7); a storage unit (read as an address translation information table (Fig. 2 @ 35)) storing the fixed identifier and an IPv4 address assigned to the transmission source by relating the fixed identifier and an IPv4 address each other (Fig.2 @ 35 is used to store "... address translation information", Column 6, Line 25); a reading unit (read as IPv4/v6 reception processing unit (Fig.2 @ 31)) reading the IPv4 address stored on the storage unit (read as an address translation information table (Fig. 2 @ 35)) and related to the fixed identifier extracted by the extraction unit (Fig.2 @ 35 is used to store "... address translation information", Column 6, Line 25); and a packet translating unit translating the IPv6 packet into the IPv4 packet with the IPv4 address read by the reading unit being set as a source address ("a header translation unit 33 for translating the header of a packet fetched by the IPv4/v6 reception processing unit 31 based on address translation information stored in an address translation information table 35 and for updating the contents of the address translation information table 35 as required",

Column 6 Lines 22-27); wherein the packet translating unit (read as translator (Fig.1 @ 55)) translates the IPv4 packet into an IPv6 packet ("the header translation unit 33 sets an IPv4-mapped-IPv6 address "::ffff:133.144.95.22" of the IPv4 host 53 as the source IP address and the previously extracted IPv6 address "::1234:5678:9abc" as the destination IP address in the packet.", Column 11 Lines 31-35). However, Hamamoto et al. fails to teach an identifier receiving unit receiving data containing a care-of address of an IPv6 terminal device and the fixed identifier indicating the IPv6 terminal device; an identifier storage unit storing the care-of address and the fixed identifier that have been received by the identifier receiving unit by relating to the care-of address and the fixed identifier each other; a care-of address acquisition unit acquiring the care-of address corresponding to a destination address of the received IPv4 packet from the storage unit and from the identifier storage unit, with the care-of address acquired by the careof address acquisition unit being set as a destination address, and with the fixed identifier related with the care-of address stored by the identifier storage unit; an IPv6 terminal device transmitting, to a home agent set in the device itself, a registration message containing a care-of address and a home address that are assigned to the device itself; and a home agent forwarding, upon receiving the registration message from the IPv6 terminal device, the received registration message to the packet translation device.

Asano et al. illustrates a case wherein the identifier receiving unit (read as home agent (Fig.2 @ 20)) receiving data containing a care-of address of an IPv6 terminal device and the fixed identifier (read as home address) indicating the IPv6 terminal

Art Unit: 2616

device ("Mobile IPv6 ... has two IP addresses as shown in FIG. 2: home address and care-of address.", paragraph [0008], Lines 1-3 and [0015]); an identifier storage unit (read as a home agent) storing the care-of address and the fixed identifier (read as a home address) that have been received by the identifier receiving unit by relating to the care-of address and the fixed identifier (read as a home address) each other (the home agent incorporates a "storage section to memorize an address management table, which defines the relationship between the home address and care-of address.", [0008] Lines 6-8); a care-of address acquisition unit (read as home agent (Fig.2 @ 20)) acquiring the care-of address corresponding to a destination address of the received IPv4 packet from the storage unit and from the identifier storage unit, with the care-of address acquired by the care-of address acquisition unit being set as a destination address, and with the fixed identifier related with the care-of address stored by the identifier storage unit ("If the Mobile IPv6 terminal 10 moves subsequently (S50), the home agent registers the invariable home address 22 and a new care-of address 23, which results from a move, in the address management table, and sends an acknowledgment packet back to the Mobile IPv6 terminal 10(S70)", paragraph [0013] Lines 11-14); an IPv6 terminal device transmitting, to a home agent set in the device itself, a registration message containing a care-of address and a home address that are assigned to the device itself ("... the Mobile IPv6 terminal 10 is turned ON and started up, it notifies a home agent 20 of its home address and care-of address (S10 -> S20).", paragraph [0013], Lines 3-5); and a home agent forwarding, upon receiving the registration message from the IPv6 terminal device, the received registration message

to the packet translation device (The home agent replies back with an ACK message to the Mobile IPv6 terminal and then Mobile IPv6 terminal forwards this message onto IPv4/IPv6 translation apparatus (Fig.15 @ 40)). It would have been obvious to a person of ordinary skill in the art to combine the home agent of Asano et al. in with the translator of Hamamoto et al. for the purpose of coupling two distinct networks having different addressing architectures. The motivation being to efficiently exchange a data communication path and couple an IPv4 terminal to intercommunicate to a Mobile IPv6 terminal and vice versa.

## Response to Arguments

5. Applicant's arguments with respect to claims 1-9 have been considered but are moot in view of the new ground(s) of rejection.

#### Conclusion

6. **THIS ACTION IS MADE NON-FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any response to this Office Action should be **faxed to** (571) 273-8300 **or mailed to**:

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

# Hand-delivered responses should be brought to

Customer Service Window Randolph Building 401 Dulany Street Alexandria, VA 22314

Any inquiry concerning this communication or early communications from the Examiner should be directed to Salvador E. Rivas whose telephone number is (571) 270-1784. The examiner can normally be reached on Monday-Friday from 7:30AM to 5:00PM.

If attempts to reach the Examiner by telephone are unsuccessful, the Examiner's supervisor, Huy D. Vu can be reached on (571) 272- 3155. The fax phone number for the organization where this application or proceeding is assigned is (571) 273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

Art Unit: 2616

Page 17

USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist/customer service whose telephone number is (571) 272-2600.

Salvador E. Rivas

S.E.R./ser

October 26, 2007

HUY D. VU

SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2600